



## S.805 Piercing eyeletting machine double feeding for eyelet and washer

Piercing eyeletting machine for the automatic application of eyelet and washer with neck on shoes, leather, clothes ecc. The machine executes at the same time the piercing of the material and the application of the two pieces ( eyelet and washer)

### MODELS :

**Electrical with -INVERTER:** tension 220 V singlephase  
Cod.80805989I

The unity is equipped with an electronic program for the complete control of the application cycle; (starting signals, end cycle antirepetition of the application, security device, ecc. are completely controlled by a microprocessor.) A lighting display with counterpieces function allows to visualise the possible anomalies that the microprocessor could find.

The security's device with mobile screen guarantees the operator incolumity protecting the application zone.

### ACCESSORIES

Support plate

Cod.80240160

Spot light point.

Cod.80165U00V



CHARACTERISTICS		MOTOR
Theor speed rate	c/1'	180
Working clearance	mm	25
Depth	mm	85
Working plane height	mm	950
Overall dimension	mm	700x700x1500
Weight	Kp	110
Motor rating	Kw	0.55 Threephases
Tension electronic implantation with INVERTER		220 V. singlephase

## IAMET Srl

Via Cascina dei Ferrandi n° 85 21044 Cavaria con Premezzo (Va) ITALIA  
TEL.+39 0331 217236 e-mail: info@iametsrl.com