



S.807 Piercing eyeletting machine with double feeding eyelet and washer.

Selfpiercing eyeletting machine for application in an automatic of eyelets and washer with neck on canvans for autotraccion, agriculture, cover tennis's fields ecc. The machine carries out contemporary the piercing of material and the application of the two pieces(eyelet and washer).

MODELS

Electropneumatic with -INVERTER: tension of 220 V singlephase, pression 5÷6 bar Cod.80807982I

The body is in standardized steel mounted on a table provided of wheels for short movements. The progress of the washer arrives through a pneumatic cylinder, the application is mecanic actioned by the motor gear group , the vibrator feeders guarantee a good capacity and continuity in alimentation.

The unity is provided with an electronic program for the complete management of the application cycle; (start signals, cycle stop, antirepetition of the application, sensors for the control passage of eyelets and washers, security switch, ecc. are entirely governed by a microprocessor.) A lighting display with counterpieces function gives the possibility to visualize the possible anomalies that the microprocceding could notice .

Fixed screen with a security switch guarantee the operator incolumity protecting the applicacion's zone, in case of removal of the same.

Version for automatic lines:

Cod.80807981I

Version manual utilisation



CHARACTERISTICS		MOTOR
Theor speed rate	c/1'	135
Working clearance	mm	10
Applicacion depth	mm	250
Working plane height	mm	1000
Overall dimension	mm	800x750x1850
Weight	Ks	300
Motor rating	Kw	0.75
Tension electronic machine with INVERTER		220 V. singlephase
Pneumatic's lines alimentation		5÷6

IAMET Srl

Via Cascina dei Ferrandi n° 85 21044 Cavarina con Premezzo (Va) ITALIA
TEL.+39 0331 217236 e-mail: info@iametsrl.com