



## S.828 Eyeletting machine

Multiple eyeletting machine with double feeder with contemporary feeding of four eyelets, suitable for application of lever mechanisms on cardboard files. The eyelet makes the hole in the material during the application.

The machine is equipped only for one type eyelet and mechanism, consequently the interax of application is fixed.

### Models

**Electric with -INVERTER:** tension 220 V singlephase, pressure 6 bar. Cod.80828988I

The electric version is provided with an electronic program for a complete application's test; (starting signals, security device, electropneumatic's valves are completely governed by a microprocessor.)

A lighting display with counterpieces function allows the visualisation of any kind of anomaly that the microprocessor could find.

A safety device with a mobile screen guarantees the operator incolumity protecting the application zone.



CHARACTERISTICS		MOTOR
Theor speed rate	c/1'	140
Working clearance	mm	12
Application's depth	mm	500
Working plane height	mm	1050
Overall dimension	mm	700x1100x1800
Weight	Ks	325
Air consumption	NI/6ba	0.25 NI/cycle
Motor rating	Kw	0.75 Threephase
Tension		220 V. singlephase

**IAMET Srl**

Via Cascina dei Ferrandi n° 85 21044 Cavaria con Premezzo (Va) ITALIA  
TEL.+39 0331 217236 e-mail: info@iametsrl.com