



## S.907 Eyeletting machine

Eyeletting machine for application of eyelets and of parts B/D of the presson buttons on leather, clothes where it is necessary to pierce the material during the application.

### MODELS

**Treadle control:** a considerable application is obtained with a slightest effort during the application

Cod.80907941/Cod.80907951

**Electropneumatic:** tension 220 V singlephase, pression 6 bar.  
Cod.80907942/Cod.80907952

**Electric with -INVERTER:** tension 220 V singlephase  
cod.809079471/Cod.809079571

The two versions are provided with an electronic program for a complete test of the cycle;(starting signals,security device, electropneumatic valves, are completely adjusted by a microprocessor).A lighting display with a counterpieces function allows the visualisation of any possible anomaly that the microprocessor could find.

A safety device with a mobile screen guarantees the operator incolumity protecting the application zone.

### ACCESSORIES :

support palte  
spot light point

Cod.80980010  
Cod.801655U00V



CHARACTERISTICS		PEDAL	ELECTROPNEUMATIC	MOTOR
Theor speed rate	c/1'	//	100	180
Working clearance	mm	15	10	
Depht	mm	180		
Working plane h	mm	970		
Overall dimension	mm	500x650x1490	550x650x1370	
Weight	Kp	70	85	95
Air consumption	NI/6ba	//	3 NI/cycle	//
Motor rating	Kw	//	//	0.37 Triphase
Tension		//	220 V. singlephase	

## IAMET Srl

Via Cascina dei Ferrandi n° 85 21044 Cavarina con Premezzo (Va) ITALIA  
TEL.+39 0331 217236 e-mail: info@iametsrl.com