



S.917-A2 Eyeletting machine

Eyeletting machine for simultaneous application of two eyelets at fixed distance on pierced parts or on leather, clothes, paper, which allows the drilling of the manufactured article during the application

MODELS

Electropneumatic: tension 220 V singlephase, pression 6 bar.
Cod.80917943/Cod.80917953

Electric with -INVERTER: tension 220 V singlephase
cod.80917948/Cod.80917958I

The two versions are provided with an electronic program for a complete test of the cycle;(starting signals,security device, electropneumatic valves, are completely adjusted by a microprocessor).A lighting display with a counterpieces function allows the visualisation of any possible anomaly that the microprocessor could find.



CHARACTERISTICS			ELECTROPNEUMATIC	MOTOR
Theor speed rate	c/1'	//	100	180
Working clearance	mm		10	
Depth	mm		180	
Working plane h	mm		970	
Overall dimension	mm		550x650x1370	
Weight	Kp		95	105
Air consumption	NI/6ba	//	3 NI/cycle	//
Motor rating	Kw	//	//	0.37 Triphase
Tension		//	220 V. singlephase	

IAMET Srl

Via Cascina dei Ferrandi n° 85 21044 Cavaria con Premezzo (Va) ITALIA
TEL.+39 0331 217236 e-mail: info@iametsrl.com