



S.920 Rivetting machine

Rivetting machine for the application of rivets on shoes, leather, clothes, ecc. The rivet, where allowed, pierces the material during the application.

MODELS

Pedal: version with mechanical action by a slight effort develops a remarkable strength during the application.

Cod.80920941/Cod.80920951

Electropneumatic: tension 220V singlephase, pression 6 bar.

Cod.80920942/Cod.80920952

Electrical with -INVERTER: tension 220 V singlephase

Cod.809209471/Cod.809209571

The two versions are equipped with an electronic program for the complete management of the application's cycle; (starting signals, security advice electropneumatic valves, etc. are entirely governed by a microprocessor.) A lighting display with counterpieces's function allows the visualisation of any possible anomaly that the microprocessor could find.

The security's device with mobile screen guarantees the operator's incolumity protecting the application's zone.

ACCESSORIES on request

Support plate

Cod.80980010

spot light (green led)

Cod.80165U00V



CHARACTERISTICS		PEDAL	ELECTROPNEUMATIC	MOTOR
Theor speed rate	c/1'	//	100	180
Working clearance	mm	15	30	
Depth	mm		180	
Working plane height	mm	1060	970	
Overall dimension	mm	500x650x1490	550x650x1370	
Weight	Kp	70	85	95
Air consumption	NI/6bar	//	3 NI/cycle	//
Motor rating	Kw	//	//	0.37 Threephases
Tension			220 V. singlephase	

IAMET Srl

Via Cascina dei Ferrandi n° 85 21044 Cavarina con Premezzo (Va) ITALIA

TEL.+39 0331 217236 e-mail: info@iametsrl.com