



## VS.920 Rivetting machine

Rivetting machine candle version for the application of rivets on the bottom of boxes and on tins and trunks. The same rivet, in case, executes the piercing on the material during the application.

### MODELS

**Pedal:** version that with a mechanic action and a slight effort develops remarkable strength during the application.

Cod.80922941/Cod.80922951

**Elettropneumatic:** tension 220V singlephase, pression 6 bar.

Cod.80922942/Cod.80922952

**Electrical with -INVERTER:** tension 220 V singlephase

Cod.809229471/Cod.809229571

The two versions are provided with an electronic program for the complete control of the application cycle; (starting signals, cycle end, antirepetition of the application, security device, ecc. are completely governed by a microprocessor.) A lighting display with counterpieces function allows to visualise the possible anomalies that the microprocessor could find.

The security's device with mobile screen guarantees the operator incolumity protecting the application zone.

### ACCESSORIES

Spot light point (Green Led)

Cod.80165U00V



CHARACTERISTICS		PEDAL	ELECTROPNEUMATIC	MOTOR
Theor speed rate	c/1'	//	100	180
Working clearance	mm	15	30	
Depht	mm		180	
Working plane h	mm	1060	970	
Overall dimension	mm	500x650x1490	550x650x1370	
Weight	Kp	70	85	95
Air consumption	NI/6bar	//	3 NI/cycle	//
Motor rating	Kw	//	//	0.37 Threephase
Tension		//	220 V. singlephase	

## IAMET Srl

Via Cascina dei Ferrandi n° 85 21044 Cavaria con Premezzo (Va) ITALIA  
TEL.+39 0331 217236 e-mail: info@iametsrl.com