

S.903P Press

Press for the utilisation of dies model "C", like eyelets, rivets, pression buttons, punches , ecc.

VERSIONS

Pedal: version with mecanical action that with a light phisical action develops remarkable application strength.

Cod. 80903P41

Electropneumatic: tension 220V singlephase, pression 6 bar.

Cod. 80903P42

Electric with -INVERTER: tension 220 V singlephase

Cod. 80903P471

Both versions are provided with an electronic program for a complete test of cycle; (starting signals, the security devices, electropneumatic's valves, are completely adjusted by a micro-processor.). A lighting display with a counterpieces's function, allows the visualisation of any possible anomaly that the microprocessor could find.

A safety device with mobil screen guarantees the operator's incolumity protecting the zone of application.

ACCESSORIES :

Support plane,
Spot light (green light Led)

Cod.80980010

Cod.80165U00V



TECHNICAL CHARACTERISTICS		PEDAL	ELECTROPNEUMATIC	MOTOR
Theor speed rate	c/1'	//	100	180
Working clearance	mm	15	10	
Depht	mm		180	
Working plane hate	mm		970	
Overral dimension	mm	500x650x1490	550x650x1370	
Weight	Kg	70	85	95
Air consumption	NI/6bar	//	3 NI/cycle	//
Motor rating	Kw	//	//	0.37 Triphase
Tension			220 V. singlephase	

IAMET Srl

Via Cascina dei Ferrandi n° 85 21044 Cavarina con Premezzo (Va) ITALIA
TEL.+39 0331 217236 e-mail: info@iametsrl.com